


GRANT - NORPAC
LINE LS-18
NORTHBOUND

SHOTS: 297,480+
HIGHRUN

ACQUISITION

Source:	Bolt 1500C
Energy:	400 cu. in.
Shot Int.:	262.5' (80m)
Fold:	60
Streamer:	3000' (914m)
Depths:	10' (3m)

PROCESSING SEQUENCE

Demultiplex	
Trace Edit	
Geometry	
Bandpass Filter	8-10-60-80 Hz
Spherical Divergence	$t^{2.0}$
Deconvolution	200 ms, 16 ms
Velocity Analysis	
Normal Moveout	
Stack	60 fold
Bandpass Filter	8-10-60-80 Hz
Time Variant Filter	
Migration	
Display	

SURVEY PARAMETERS

Shot Point Interval	262.5' (80m)
Streamer Length	3000' (914m)
Number of Channels	60
Group Interval	50' (15m)

LINE LOCATION
NORTHBOUND
Shot Point 297,480



NOTES

LIMITED RIGHTS LEGEND

Miscellaneous Paper SI-2: Seismic Reflection Profiles of Glacial Sediments and Bedrock Structures Beneath Whitefish Bay in Lake Superior
Plate 6: Line 18
1991

These profiles have been photomechanically reduced from an original plotted scale of 1 second = 2.2 inches, as a result, some of the image may have been degraded.

Published by and available from

SAGEOS, University of Wisconsin–Extension Geological and Natural History Survey
Attention: Publications Sales Desk
3817 Mineral Point Road, Madison, Wisconsin 53705

3 Kilometers

SCALES

1 second